


□ □ □ □ □ □ □ □ □ □ □ □

[illegible][illegible]


**2**


[illegible]



□□□ □      □□ □ □ □ □ □ □ □□ □ □ □ □ □ □ □ □  
□ □ □□ □ □ □ □ □ □ □ □ □ □ □ □ □ □

000 0  
 00 0000 (0 0 00 0 00 0 00 0 0  
 0 0 0 0 0 0000 0 0 0 0 0000 0 0 0 0 0  
 0 0 0 0 0 0 0 000 0 0  
 0 0 0 0 0 0 0 0000 0 0 0000

[illegible][illegible]

Diagram illustrating a 16-bit bus structure. The bus is divided into three sections: a 2-bit section (top row), an 8-bit section (middle row), and a 6-bit section (bottom row). The 8-bit section is highlighted in red and labeled **AM 8**.

**A** □ □ □ □ □ □ □ □ □

E-mail [redacted]  
☆ [redacted] E-mail [redacted]  
  
✳ [redacted] E-mail [redacted], [redacted]  
[redacted] ito.ed.jp [redacted]  
[redacted]  
✳ [redacted]



- ①
- ②
- ③
- \* H

**B**

**FAX**

[ PDF ]

[illegible]

☐ ☐ ☐☐ ☐☐ ☐☐ ☐



□ □ □	□ □ □
□□ □□ □	□□ □□(□ ) □□ □□(□ )
□□ □□ □	□□ □□(□ ) □□ □□(□ )
□□ □□ □	□□ □□(□ ) □□ □□(□ )
□□□ □□□ □	□□□ □□(□ ) □□□ □□(□ )
□□□ □□□ □	□□□ □□(□ ) □□□ □□(□ )
□□ □(□ )	□□ □□(□ ) □□ □□(□ )
□□ □(□ )	□□ □□(□ □ □□ □□(□ )